



TRUCCSA

Revestimientos y Morteros especiales para la Construcción

Atención al Cliente

968 081 080

TECHNICAL DATA SHEET

ACOTEL

Finishing pigment

COMPOSITION

Pigments
 Aggregates
 Additives

CHARACTERISTICS

Excellent workability.
 Very good adherence to sound substrates.
 Can be applied directly onto the surface.

COLOUR RANGE

We currently have a range of 175 colours available. Special colors are available on request.

SUBSTRATES

Textured mortars.

CONSERVATION

Store in a dry place.

STORAGE

Shelf life is approximately 12 months from date of manufacture if stored in unopened original packing in dry conditions.

PACKAGING

1 kg. plastic storage jar.

DESCRIPTION

Inert and UV radiation-resistant iron oxid-based pigments.

HOW TO USE

Add water until it becomes liquid and apply with spray gun, by brush or with a sponge onto textured coating. The substrate must be completely dry.

If the shading applied is not what is wanted, wash it off with water before it dries.

To obtain various color shades or tones apply different coats with different ACOTEL colors.

At last, apply Truccsa IMPER W to fix the pigment.

PRECAUTIONS

The substrate must be clean, free of loose parts, paints and grease. Do not apply at temperatures below +5° C or above +35° C.

The product must not be applied to frozen or thawing supports. If the coating must be applied in adverse weather conditions, it is essential to protect both the working area and finish before and after application.

The substance has not qualified like dangerous

It is not considered to be dangerous, in normal conditions of use, neither for the persons nor for the environment.

For further information consult Material Safety Data Sheet (MSDS)

The information released in this document is based upon our present knowledge