



# TRUCCSA


Revestimientos y Morteros especiales para la Construcción

Atención al Cliente

968 081 080

## TECHNICAL DATA SHEET

### GLOXER C1 Outer



#### DESCRIPTION

Cementitious adhesive with good workability, for laying ceramic tiles and floors inside and outside.

Suitable for laying ceramic tiles with a medium-high absorption rate.

#### COMPOSITION

Cement based product, selected aggregates, resins and additives that provide a quality and excellent adhesion.

#### CHARACTERISTICS

Adhesive suitable for indoor and outdoor flooring.

Special ceramic placement absorption medium-high.

A good adherence product and non slip

#### HOW TO USE

Mix the product with 25% water, manually or with a low-speed electric mixer (500rpm) until a homogenous blend is achieved. Let the mix to stand for a few minutes and then stir the mix before applying. Spread the mix with a notched trowel (see the notched-trowel panel) in a maximum surface of 2 m<sup>2</sup>, because, the shorter the time between the spreading of the mix and the laying of the tiles, the higher will be the adhesion.

Lay the tiles onto the adhesive and ensure that a firm pressure is applied to achieve good contact with the adhesive.

Special care must be given to all construction joints (expansion, contraction and perimeter corner joints) as well as to the joints between the cement slabs (minimum 2 mm.)

On floor areas larger than 30 m<sup>2</sup>, leave partition joints.

On interior floorings larger than 15 m<sup>2</sup>, leave perimeter joint between the floor and the wall or pillar.

Joints must be grouted after 24 hours on vertical surfaces and after 48 hours on floorings.

#### PRECAUTIONS

The substrate must have good flatness, otherwise, it's recommendable to smooth the surface with the same product at least 48 hours before applying the product and laying the tiles.

If the product must be applied in hot or windy weather or onto high absorption substrate, it's recommendable to wet the substrate.

The substrate must be clean, free of loose particles, paint and grease.

**DO NOT APPLY ONTO PLASTER.**

For gypsum based substrates, use GLOXER C1E YESO.

Do not apply at temperatures below +5° C or above +35° C.

For further information consult Material Safety Data Sheet (MSDS)

#### COLORS

White and Grey.

#### SUPPORTS

Conventional Supports in walls and floors inner and outer.

#### CONSERVATION

Store in a dry place.

#### STORAGE

Shelf life is approximately 12 months from date of manufacture if stored in unopened original packing in dry conditions.

#### PACKAGING

25 kgs. 3 ply paper-plastic-paper sacks.

Shrink-wrapped pallets of 1.400 kg.(56 sacks)



# TRUCCSA

Revestimientos y Morteros especiales para la Construcción

 Atención al Cliente  
**968 081 080**

 TECHNICAL SHEET  
**GLOXER C1 Outer**
**TECHNICAL DATA**

	Value	Regulation
Initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$	UNE EN-1348 8.2
Tensile adhesion strength after water immersion	$\geq 0,5 \text{ N/mm}^2$	UNE EN-1348 8.3
Tensile adhesion strength after heat ageing	$\geq 0,5 \text{ N/mm}^2$	UNE EN-1348 8.4
Tensile adhesion strength after freeze thaw cycles	$\geq 0,5 \text{ N/mm}^2$	UNE EN-1348 8.5
Open time (adherence 20 mins)	$\geq 0,5 \text{ N/mm}^2$	UNE EN-1346

These values are the results obtained in laboratory tests

 ☐ According to standard UNE-EN 12004:2008  
 Clasification: Type C1 (UNE-EN 12004:2008)

**TECHNICAL FEATURES**

Aspect	White or Gray powder
Open time	30 min aprox.
Adjustment time	20 min aprox.
Lifetime of the paste	2 h.
Grouting time	24 h.
Ready for light foot traffic	from 24 to 48 h.
Approximate yield.	4 to 5 kg m <sup>2</sup> .

**NOTCHED TROWELS TABLE**

Format	Notched trowel	BONDING
< 100 cm <sup>2</sup>	U4 (4 x 4 x 4)	Single
≤ 450 cm <sup>2</sup>	U6 (6 x 6 x 6)	Single
≤ 900 cm <sup>2</sup>	U6 (6 x 6 x 6)	Double
	U9 (9 x 9 x 9) / 110	Single
>900 cm <sup>2</sup>	U9 (9 x 9 x 9) / 110	Double

**NOTE:**

All data shown on this page is indicative and consistent with laboratory tests. The company is not liable for misuse of the product by the consumer.

REV.00



# Truccsa

Revestimientos y Morteros especiales para la Construcción

Atención al Cliente

968 081 080

TRUCCSA SIGLO XXI S.L. CIF B30767438 Inscrita en el R.M. de Murcia, Tomo 1991, Sección 8ª, Folio 86, Hoja MU-47188, Inscripción 1ª

Truccsa

Budapest , parcela 42 Polígono Industrial Cabezo Beaza Apdo. de correos 2192 CP 30353  
Cartagena (Murcia) SPAIN T 968 08 10 80 F 968 52 46 98 e-mail: [truccsa@truccsa.com](mailto:truccsa@truccsa.com)

[www.truccsa.com](http://www.truccsa.com)