

## GLOXER C2TE FLEXIBLE

### DECLARATION OF PERFORMANCE

In accordance with European Construction Product Regulation (RPC) nº 305/2011

Nº DdP ES-TC0014

1. *Unique identification code of the product-type:*

GLOXER C2TE FLEXIBLE

2. *Type, batch or serial number or any element allowing identification of construction product as required pursuant to Article 11 (4):*

Cementitious Adhesive. Type C2TE (UNE EN 12004:2008)  
Check the name, batch and date of manufacture on the packaging.

3. *Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:*

Flexible tile adhesive for ceramic tiles and placement of interior and exterior flooring of all types of ceramics. Especially suitable for laying tile over tile, for flooring with radiant heating and baseboards.

4. *Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant to Article 11(5):*

TRUCCSA

C/ Budapest, parcela 42  
Polígono Industrial Cabezo Beaza  
CP 30353 Cartagena (Murcia)

truccsa@truccsa.com

5. *Where applicable, name and contact address of the authorized representative whose mandate covers the task specified in Article 12(2):*

Not applicable

6. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

System 3

7. *In case of the declaration of performance concerning a construction product covered by a harmonized standard:*

C2TE (UNE-EN 12004:2008)

*Name and identification number of the notified body:* APPLUS-LGAI Technological Center S.A.,  
notified with the nº 0370.

*Procedure for attesting:* Initial type tests

*Evaluation system:* 3

## GLOXER C2TE FLEXIBLE

8. *In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*

Not applicable

9. *Declared performance:*

	Value	Regulation
Initial tensile adhesion strength	$\geq 1 \text{ N/mm}^2$	UNE EN-1348 8.2
Tensile adhesion strength after water immersion	$\geq 1 \text{ N/mm}^2$	UNE EN-1348 8.3
Tensile adhesion strength after heat ageing	$\geq 1 \text{ N/mm}^2$	UNE EN-1348 8.4
Tensile adhesion strength after freeze thaw cycles	$\geq 1 \text{ N/mm}^2$	UNE EN-1348 8.5


*Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:*

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Miguel Fernández Meca, Technical Director

Cartagena, March 04th, 2014