



TRUCCSA

Revestimientos y Morteros especiales para la Construcción

Atención al Cliente

968 081 080

TECHNICAL DATA SHEET

IMPER W

Water - based finishing liquid

DESCRIPTION

Product based on styrene acrylic copolymer that improves the water resistance to external/internal coatings.
 Ready-to-use product.

APLICACIONES

For protection, curing and sealing of mortars.
 It also can be used as a primer coating for highly porous surfaces.

HOW TO USE

Apply directly onto the surface being treated. It can be applied by spraying or using a brush or roller. You should wait for the mortar to dry (approximately 24 hours). A single application is usually enough. Make sure that the layer applied is as uniform as possible and in the recommended amount.

PRECAUTIONS

Do not leave containers with the product open, this will prevent surface drying.
 Although it does not contain solvents, it is preferable to have appropriate ventilation where the work is being done. The use of gloves and safety glasses is recommended.
 Do not apply at temperatures below +10° C or above +30° C.
 For further information consult Material Safety Data Sheet (MSDS)

TECHNICAL DATA

Aspect	Milky white liquid
Yield	8-10 m ² /L
Solid content	25%
Dry to the touch	1-2 hours
Completely dry	24 hours
Solvent	Water

The information released in this document is based upon our present knowledge

COMPOSITION

Water
 Acrylic copolymers
 Additives

SUBSTRATES

Mortars, concrete, highly porous surfaces.

STORAGE

Shelf life is approximately 6 months from date of manufacture if stored in unopened original packing in dry conditions.

PACKAGING

5 lts and 25 lts plastic drums