

Atención al Cliente 968 081 080

TRUCCAL

DECLARATION OF PERFORMANCE

In accordance with European Construction Product Regulation (RPC) no 305/2011

Nº DdP ES-TE0022

1. Unique identification code of the product-type:

TRUCCAL

Type, batch or serial number or any element allowing identification of construction product as required pursuant to Article 11 (4):

Onecoat cladding mortar type OC-CS III-W1. Check the name, batch and date of manufacture on the packaging.

Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

For application as decorative finish, inside and facades and waterproofing.

Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant to Article 11(5):

TRUCCSA

C/ Budapest, parcela 42 Polígono Industrial Cabezo Beaza CP 30353 Cartagena (Murcia)

truccsa@truccsa.com

Where applicable, name and contact address of the authorized representative whose mandate covers the task specified in Article 12(2):

Not applicable

System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

UNE-EN 998-1:2010

Name and identification number of the notified body: APPLUS-LGAI Technological Center S.A., notified with the no 0370.

Procedure for attesting: Initial type tests

Evaluation system: 3

Issued document: Essay report nº 21/24486-152-S

Budapest, parcela 42 Polígono Industrial Cabezo Beaza Apdo. de correos 2192 CP 30353 Cartagena (Murcia) SPAIN T 968 08 10 80 F 968 52 46 98 e-mail: truccsa@truccsa.com

Atención al Cliente 968 081 080

In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable

Declared performance:

	Value	Regulation
Reaction to fire	A1(fireproof)	UNE-EN 13501-1:2002
Adhesion	≥0,3 N/mm²	UNE-EN 1015-21:2003
Resistance to adherence	В	UNE-EN 1015-21:2003
Resistance to compression	≥ 3,6 N/mm ²	UNE-EN 1015-11:2000
Water absorption coefficient	W1	UNE-EN 1015-18:2003
Water vapour permeability	μ ≤ 8	UNE-EN 1015-19:1999
Water permeability	≤ 1 ml/cm ³	UNE-EN 1015-21:2003

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufactured identified in point 4.

Signed for and on behalf of the manufacturer by:



Miguel Fernández Meca, Technical Director

Cartagena, March 20th, 2014

